

D-Link®

Indigenous SERIES

DCS-F5614-L1

High-definition professional surveillance and security solution, suitable for small and medium enterprises.

5 Mega Pixel Dome IP Camera with Audio



DCS-F5614-L1

Key Features



1/3" 5MP
Progressive CMOS



3.6mm
Lens



PoE
Enabled



H.264 & H.265,
Dual-Stream



30
Meters IR

Specifications

Parameters	Specification
Image Sensor	1/3" 5MP Progressive CMOS Sensor
Effective Pixels	1920(H)x1080(V)
Minimum Illumination	Color: 0.01 Lux @F2.0, B/W: 0.001 Lux@F1.2
S/N Ratio	>60dB
IR Distance	IR Distance 30Mtr
Shutter Speed	Auto, Manual Mode: 1/50 sec 1/10000 sec
DWDR	Yes
IR On/Off Control	Auto/ Manual
IR LEDs	3 Array LEDs
Lens	
Lens Type	Fixed
Mount Type	M12
Focal Length	3.6mm Lens
Max. Aperture	F1.2
Angle of View	Horizontal Angle- 72°, Vertical Angle- 54°, Diagonal Angle- 86°
Focus Control	Fixed
Video	
Compression	H.265 / H.264
Streaming Capability	2 Streams
Resolution	5MP (2592X1944) / 1080P(1920x1080) / 1.3M(1280x960) / 720P(1280x720) / D1(704x576/704x480) / VGA (640x480) / CIF (352x288/352x240)
Streams	Mainstream: 5MP (2592X1944) @20FPS/ 4MP (2560X1440)/2MP (1920x1080) @25 /30FPS, Sub Stream: D1 (704x576)/VGA (640x480)/ CIF (352x288) @25/30FPS

Auth. Project Partner :


TechnoHEAD
INNOVATION BY INTEGRATION

D-Link Indigenous series range of IP Surveillance solution includes



Specifications

Parameters	Specification	Parameters	Specification
Frame Rate	5MP@20fps, 2MP@ 25/30fps	Safety	
Bit Rate Control	CBR/VBR	ONVIF Authentication	ON, OFF
Bit Rate Range	221Kbps~8Mbps	RTSP Authentication	Digest, None
Day/Night	Automatic/Color/Black and white	Audio	
Exposure Mode	Automatic/Manual-(1/50-1/10000)	Compression	G.711A/J
BLC Mode	On/Off	Network	
Profiles	Auto, Low Light Priority, High Light Priority	Ethernet	1 x RJ45, 10/100M adaptive Ethernet interface
White Balance	Indoor/Outdoor/Automatic	Protocol	TCP/IP, HTTP, UDP, RTSP, FTP, DHCP, DDNS, NTP, SMTP, UPnP, IPv4, IP filter
Automatic Gain Control	Yes	Interoperability	ONVIF Profile S
Noise Reduction	Auto, 2D/3DNR (1-5 Levels)	Max. User Access	30 Users
Electronic Image	Support	Edge Storage	Local PC for instant recording, One click Snapshot, One clicks triple Snapshot
I frame Rate	1 to 20	Web Viewer	IE, Chrome, Firefox, Safari
Smart IR	Support	Management Software	D-Link Vision VMS
Digital Zoom	16X, Area selection with Mouse	Smart Phone	Supports D-Link Vision APP for iPhone, Android
Anti-Flicker	On/Off	Interface	1 In
White Balance	Yes	Audio	
AE reference	1-255 Level	General	-30° C ~ +60° C /
AE Sensitivity	1-10 Level	Operating Conditions	Less than 90% RH -30° C ~ +60° C /
Flip	Off / On	Storage Conditions	Less than 90% RH
IR reverse	Support	Ingress protection	NA
Mirror	Off / On	Vandalism protection	DC 12V / 1Amp, PoE
Text Overlay	Title, Date & Time, Weekday	Power Rating	Max 12W
Privacy Masking	Yes (4 zones)	Power Consumption	84.42mm(H) x 109.85mm(W), 200 g
Events	Yes	Dimension & Weight	
Motion Detection	Support	Product Certification	Safety: CE, BIS
Video Tempering	Pre Record- 5-30 Sec, Post		
Event Recording	Record 1-120 Minute		
Smart Functions	Human Detection, Line Crossing & Area Intrusion		
Event Actions	Record alarm, Linkage alarm output, Sound alarm, Email link, Upload FTP, Snapshot		
PTZ			
Pan/Tilt Range	Pan:0° ~360°; Tilt:0° ~90°; Rotation:0° ~360°		

Auth. Project Partner :



Solutions Design | Supply | Installations | AMC | Services

TECHNOHEAD Security IT & Telecom Projects LLP

Address :- 706 Siddharth Building 96, Nehru Place, New Delhi – 110019, India

Mobile :- +91 8527590286, 9312286189

Email :- info@technohead.in Website : www.technohead.in

- DCS-F5612-L1: 2MP Mega Pixel Dome IP Camera with Audio
- DCS-F5712-L1: 2MP Mega Pixel Bullet IP Camera with Audio
- DCS-F5614-L1: 5MP Mega Pixel Dome IP Camera with Audio
- DCS-F5714-L1: 5MP Mega Pixel Bullet IP Camera with Audio
- DNR-F5104-M5: 4 Channel 1 SATA NVR
- DNR-F5108-M5: 8 Channel 1 SATA NVR
- DNR-F5216-M5: 16 Channel 2 SATA NVR
- DNR-F5232-M5: 32 Channel 2 SATA NVR